



Donaldson Part No: **P506063**

**Fluid Compatibility: Safe for use with all diesel fuels and lubricants**

**Replacement Breather Element: P923075**

The Dual T.R.A.P. Breather assembly with huge dirt holding capacity protects the fluids in your storage tanks from airborne particulate contamination and ambient moisture.

It combines a premium quality relief valve protecting the tank against excess vacuum and pressure forces, to enable compliance with API2000 and is equipped with a high quality vacuum gauge utilising Magnahelix technology to allow accurate measurement of the level of air flow restriction during normal operational fluid dispensing conditions.

### SPECIFICATIONS

<b>Efficiency</b>	97% efficient @ 3 micron
<b>Max Flow Range</b>	1,000 lpm
<b>Standard PV Settings:</b>	3.1" H <sub>2</sub> O Vacuum and 6.7" H <sub>2</sub> O Pressure
<b>Operating Temperature</b>	-40 to 93°C
<b>Indicator</b>	12450-400 Magnahelix gauge
<b>Complete Assembly Dimensions</b>	Height: 656 mm Width: 360mm Depth: 445 mm
<b>Connection</b>	2" BSPT socket
<b>Indicator Port</b>	1/8" NPT
<b>Replacement Filter</b>	P923075 x 2

### APPLICATIONS

- Most tanks up to 1,000 lpm
- Confirm your tanks safe pressure and vacuum ratings to ensure API2000 compliance

### FEATURE & BENEFITS



#### High capacity vacuum and pressure relief valve

- Meets API2000 requirements
- Protects the tank against excess vacuum and pressure forces
- Premium quality
- Corrosion resistant



#### Magnahelix gauge

- Indicates operational vacuum or pressure during flow
- Premium quality
- Corrosion resistant
- Supplied with surface mount bracket

