



Donaldson Delivers

DUAL HEAD CLEAN & DRY DIESEL KIT

Ideal for all diesel fuel applications up to 375lpm
Maximum working pressure: 350psi

CLEANLINESS IS CRITICAL

A small amount of contamination can severely damage your engine.

Modern diesel engines are being built to increasingly stringent specifications with finer operating tolerances. They require clean, dry fuel for optimum combustion, maximum power and the lowest emission levels. Dirt and water are the enemies of High Pressure Common Rail fuel systems and can dramatically reduce the service life of fuel system components.

The kit uses two high performance filter sets, in series, to clean your diesel fuel ready for use.

The first filter removes particulate contamination from diesel. Rated at $<4\mu\text{m}@\beta 2000$ (99.9% single pass), it is designed to target a cleanliness of ISO 14/13/11 in a single pass. The second filter uses a super absorbent polymer (SAP) that will not allow free water to pass. This combination of filters will ensure that your diesel is both clean and dry, for a maximum performance.



 **PERFORMANCE**
FULL FLOW - HIGH EFFICIENCY - LONG LIFE







 **QUALITY**
HEAVY-DUTY AND BUILT TO LAST

 **RELIABILITY**
MEETS OR EXCEEDS OEM SPECIFICATIONS



Suitable for service vehicles, mobile tanks, fixed bulk tanks in the industrial, agricultural, mining and transport markets

Part No: **X900018**

| Kit Contents | | | |
|-------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------|-----|
| Image | Part No | Description | Qty |
|  | P568583 | CFLS Dual Head 1 1/2" SAE 4 Bolt Code 61 flange | 2 |
|  | P506071 | Thread Flange 1 1/2" SAE 4 Bolt Code 61 Length: 100mm x 85mm x 36mm Thread Size: 1 1/2" BSPP | 2 |
|  | P506101 | Flange Connection Kit | 1 |
|  | DBB8666 | Dimensions O.D: 127mm, Length: 362mm < 4 Micron @ Beta 2000 | 2 |
|  | DBB0248 | Dimensions O.D: 127mm, Length: 362mm SAP Water Absorbing Filter (not suitable for ethanol or ethanol blends) | 2 |
|  | P573681 | Pressure Gauge 0-60 psi Thread Size: 1/8" NPT Face Diameter: 42mm | 2 |
|  | P573682 | Gauge Adapter Inlet Diameter: Male 9/16" - 18 UNF" Outlet Diameter: Female 1/8" NPT Length: 43mm | 2 |

OPTIONAL TRAP BREATHERS

FOR MOBILE TANKS:



P766645 - 3/4" BSP Anti-splash T.R.A.P.
P766646 - 1" BSP Anti-splash T.R.A.P.

FOR FIXED TANKS TO 1000 LITRES:



P564669 - 1" NPT T.R.A.P.
P565616 - Bayonet T.R.A.P.

FOR FIXED TANKS OVER 1000 LITRES:



P923075 - T.R.A.P. Breather Filter
DFF0078 - T.R.A.P. Breather Assembly



Application/Cross-Reference/Attribute Search
shop.donaldson.com

Find your filter or any other type of Donaldson filter using Donaldson search tool at: shop.donaldson.com



Donaldson Australasia Pty Ltd
PO Box 153, Wuyong NSW 2259

Freecall: 1800 345 837
Ph: +61 2 4350 2000
Fax: +61 2 4351 2036

Donaldson New Zealand
PO Box 14-770, Panmure 1741 Auckland

Ph: +64 9 579 2790
Fax: +64 9 579 0322

www.donaldson.com

Brochure No. Dual Clean & Dry Kit (07/18)

© 2018 Donaldson Company, Inc. All rights reserved. Donaldson Company, Inc. reserves the right to change or discontinue any model or specification at any time and without notice. Printed in Australia.